

ACCESSORIES

REFERENCE: 50-41

ROPE AUTOMATIC FALL ARRESTER

Descripción

Certified carabiner made of heavy-duty steel with triple action self-closing device, used to make short connections with other devices, ropes and elements that are part of the fall protection system.

50-41-2: medium size self-closing device carabiner with 24mm opening.

50-41-3: small size self-closing device carabiner with 12mm opening.



50-41-2

General information:

-The accessory Ref. 50-40A is part of the Personal Fall Protection System and its use is recommended when carrying out work at heights (according to requirements established by Colombian Government law, resolution 1409 de 2012).



50-41-3

Technical information

ELEMENTO	Q	REQUISITOS NORMATIVOS			MATERIAL	COLOR	PESO
		NORMA	RESISTENCIA	VALOR REAL			
50-41-2		ANSI/Z359.12-2009	Mayor a 22.2 kN	50 kN	Acero	Zincado Amarillo	299 g
50-41-3		ANSI/Z359.12-2009	Mayor a 22.2 kN	40 kN	Acero	Zincado Amarillo	215 g

IMPORTANT:

This element must not be used as implement for extreme sports.

Technical features

- 100% Made of topalized protection steel.
- Compatible with rope and Fall protection system elements.
- Friction and high temperature resistant.
- Compatible with safety hooks.
- Safety system with triple action.

Aplicaciones

- Fall Protection System connection with D rings, safety hooks, ropes and anchorages)
- Use in sectors such as:

*Mining
Industry
Installations
Construction
Cabling
Painting
Outside cleaning
Specialized work*

Advertencias

- The service life of this product is given by the use, care, maintenance and proper storage.
- Service life timeline starts at the moment the product is subjected to first use. It should not be used manufacturing time to determine service time.
- It must be to follow instructions included within the product at the moment it is dispatched.
- Before using this product, make a correct calculation of the requirements needed (height, activity, kind of work) to be sure the product is suitable.
- Do not alter the product.
- This product is not fire, chemic or electric resistant, therefore take the necessary precautions for use in environments that have these sources of risk.
- This product offers limited protection in highly corrosive environments, therefore take the necessary precautions to protect the product and prolong its service life.
- This product has not sunlight protection so avoid long sun exposure which could cause discoloration on the product. Take the necessary precautions to protect the product and prolong its service life.
- The user must be trained to use this equipment, therefore they must meet the training requirements established by Colombian Government law (resolucion 1409 de 2012).

Warranty Policies

- This product is certified under quality standards ANSI Z359. 12-2009
- Warranty applies ONLY before first use due to manufacturing defects or defects of any of its parts.
- As manufacturing defects: opening device malfunction, brake system malfunction, absence of brake parts.

The product will be not accepted if presents:

- Paint contamination.
- Presence of cuts or excessive abrasion.
- Damage such as sharp edges, deformation, chemical corrosion or any change.
- Damage produced by excessive dirt, wrong storage, excessive lubrication and abusive use.
- Alteration, Absence of parts, evidence of damage due to improperly performed functions, or by mechanical devices and connectors.
- Damage produced by fire, flames or any element that could burn the brake.

Note:

- It is important to read all the information included in the instruction guide before using any product.
- The company is not responsible for any product that has been repaired outside its facilities.
- Exchange of products due to low rotation is not accepted.

IMPORTANT:

Service life timeline starts at the moment the product is subjected to first use.