

LIFE LINE

REFERENCE: PE-15S

RETRACTABLE LIFE LINE

Description

15 m length retractable lifeline, manufactured with high impact polymer casing and stainless-steel cable of 3/16 inch (4.8mm diameter)

General Information

- -Retractable lifeline PE-15S is part of the Personal Fall Arrest System -The connector for the PE-15S model complies EN 362 and its use is recommended when carrying out work at heights. requirements and incorporate a swivel device used in the (according to requirements established by Colombian Government connection with the user. law, resolucion 1409 de 2012).
- -This equipment is especially used as a part of Fall Arrest System, reducing the force of vertical impact on the body by limiting fall distance.
- -This equipment complements all EPI Fall Protection System products.

-This equipment is one person use only.

Safety Carabiner

carabiner made of heavy-duty steel with triple action self-closing device and 17mm opening, which allows safe connection to the fall arrest system.



Maximum weight allowed: 140 kg.



maximum angle from vertical axis: 40°



Do not use horizontally.

Label and Protective casing

The label contains details product number, technical data and use information. The casing is made of a resistant and low weight polymer, protecting the internal mechanisms.



Steel cable

Stainless steel cable of 7x19 and 4.8mm diameter.

3/4 Safety hook

Swivel hook with double safety system and 25mm opening to carry out connection with dorsal ring of the harness.



EN 360:2002

RETRACTABLE LIFE LINE

certificado N° GB/PP 234811

IMPORTANT:

This element must not be used as implement for extreme sports with freefall.